Minor

Total marks: 30 Total time: 2 hours

1. **[3.5 marks]** An angular plate in a state of plane stress is subjected to uniform tensile pressure of 20 MPa on its sides as shown in the figure below.



If the state of stress is uniform (i.e. it does not vary from point to point) throughout the plate, determine

- (a) the traction vectors (expressed in $e_1 e_2$ coordinate system) on planes AB and BC,
- (b) the stress components σ_{11} , σ_{22} , and τ_{12} at any point in the plate.
- 2. [6 marks] Consider a closed-end thin-walled cylindrical shell on internal radius R and thickness t with an internal pressure p. show that the principal stresses in the cylinder wall (not the end cap walls), in cylindrical coordinates (r, θ, z) , are given by:



What is the maximum shear stress in the $\theta - z$ plane? Is it equal to the absolute maximum shear stress?

3. [7 marks] The deviatoric stress state is used in theories of failure since it is a measure of those stresses that produce only distortional (and no volume) changes in a body. Consider the state of stress (in MPa):

$$\left[\underline{\underline{\sigma}}\right] = \begin{bmatrix} 55 & 0 & 24 \\ 0 & 46 & 0 \\ 24 & 0 & 43 \end{bmatrix}$$

- (a) Determine the deviatoric stress matrix, $\left[\underline{\underline{\sigma}}_{dev}\right]$. (1 mark)
- (b) Compute the stress invariants of the stress tensor $\underline{\sigma}$ and those of deviatoric stress tensor $\underline{\underline{\sigma}}_{dev}$. (2 marks)
- (c) Compute the principal directions of the deviatoric stress tensor $\left[\underline{\sigma}_{dev}\right]$ and the stress tensor $\left[\underline{\sigma}\right]$. How are they related? How are the *absolute* maximum shear stresses related in both cases? (4 marks)
- 4. [3.5 marks] Sketch the Mohr's circle for stress for each of the following cases of plane stress.



5. [5 marks] Consider a cantilever beam (with one end free and another end fixed) with a vertical load P applied to the free end of the beam. At the fixed end, the displacements and the slope are zero, i.e., $u_x(L,0) = u_y(L,0) = \frac{\partial u_y}{\partial x}(L,0) = 0$. The corresponding strain field at any point in the beam is given by:

$$\epsilon_{xx} = \frac{Pxy}{EI}, \quad \epsilon_{yy} = -\nu\epsilon_{xx},$$

$$\epsilon_{xz} = \epsilon_{yz} = \epsilon_{zz} = 0,$$

$$\epsilon_{xy} = \frac{P}{4GI}(h^2 - y^2)$$

Check if the strain field is compatible or not. Using the given information, find out the displacement fields $u_x(x, y)$ and $u_y(x, y)$.

- 6. [5 marks] A thin rectangular sheet is strained with uniform strain components: $\epsilon_{xx} = 0.001$, $\epsilon_{yy} = -0.001$, $\gamma_{xy} = 0.001$. All other strain components are zero implying it is a plane strain condition.
 - (a) Draw Mohr's circle for this case. (2 marks)
 - (b) How much will be the percentage change in the area of the thin sheet? (1 mark)
 - (c) Which line elements undergo maximum and minimum normal strain? (1 mark)

2

(d) What will be the orientation of the two perpendicular lines in the plane of the sheet that undergo maximum angle change between them? (1 mark)



On plane BC	
$\begin{bmatrix} \mathbf{T}^{n_{\mathbf{BC}}} \end{bmatrix}_{\begin{pmatrix} \mathcal{C}_{\mathbf{I}} \\ \mathbf{e}_{\mathbf{z}} \end{pmatrix}} =$	$\begin{bmatrix} T_1^{n_{BC}} \\ T_2^{n_{BC}} \end{bmatrix}$

$$T_{1}^{n_{BC}} = T_{1}^{n_{BC}} \cdot \underline{e}_{1} \qquad T_{2}^{n_{BC}} = T_{2}^{n_{BC}} \cdot \underline{e}_{2}$$

$$= 20 \cos 40^{\circ} = 20 \sin 40^{\circ}$$

$$= 15 \cdot 32 \text{ MPa} \frac{1}{2} = 12 \cdot 86 \text{ MPa} \frac{1}{2}$$

$$\frac{On \text{ plane AB}}{\left[\mathbf{T}^{n_{AB}} \right]_{\left(\begin{array}{c} e_{i} \\ e_{z} \end{array}\right)}} = \begin{bmatrix} \mathbf{T}_{i}^{n_{AB}} \\ \mathbf{T}_{z}^{n_{AB}} \end{bmatrix}$$

 $T_{1}^{n_{AB}} = \underline{T}^{n_{AB}}, \underline{e}_{1} \qquad T_{2}^{n_{AB}} = \underline{T}^{n_{AB}}, \underline{e}_{2}$ $= 20 \cos 180^{\circ} \qquad = 20 \cos 90^{\circ}$ $= -20 \text{ MPa} \qquad \boxed{1/2} \qquad = 0 \qquad \boxed{1/2}$ For a uniform state of stress $\left[\underline{\Phi}\right]_{\left(\underline{e}_{2}^{1}\right)} = \left[\begin{array}{c} \sigma_{11} & \sigma_{12} \\ \sigma_{12} & \sigma_{22} \end{array}\right]$ $\left[\underline{T}^{n_{AB}}\right] = \left[\begin{array}{c} \underline{\Phi}\right] \left[\underline{\Psi}_{AB}\right] \qquad , \qquad \left[\begin{array}{c} \underline{T}^{n_{BC}}\right] = \left[\begin{array}{c} \underline{\Phi}\right] \left[\underline{\Psi}_{BC}\right]$

where all vectors and matrices are expressed in (e1-e2) coor sys

$$\begin{bmatrix} \underline{n}_{AB} \end{bmatrix}_{\begin{pmatrix} e_1 \\ e_2 \end{pmatrix}} = \begin{bmatrix} -\sin 40^{\circ} \\ \cos 40^{\circ} \end{bmatrix}, \qquad \begin{bmatrix} \underline{n}_{BC} \end{bmatrix}_{\begin{pmatrix} e_1 \\ e_2 \end{pmatrix}} = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

For
$$\underline{T}^{n_{BC}}$$
,

$$\begin{bmatrix} 15 \cdot 32 \\ 12 \cdot 86 \end{bmatrix} = \begin{bmatrix} \overline{\sigma_{1}} & \overline{\tau_{12}} \\ \overline{\tau_{12}} & \overline{\sigma_{22}} \end{bmatrix} \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$

$$\Rightarrow \quad \overline{\tau_{12}} = 15 \cdot 32 \text{ MPa} \quad \boxed{\gamma_{2}}$$

$$\sigma_{22} = 12 \cdot 86 \text{ MPa} \quad \boxed{\gamma_{2}}$$

For
$$\underline{T}^{n_{AB}}$$
,

$$\begin{bmatrix}
-20 \\
0
\end{bmatrix} = \begin{bmatrix}
\sigma_{11} & \tau_{12} \\
\tau_{12} & \sigma_{22}
\end{bmatrix}
\begin{bmatrix}
-\sin 40^{\circ} \\
\cos 40^{\circ}
\end{bmatrix}$$

$$\overline{\sigma_{11}} (-\sin 40^{\circ}) + \tau_{12} \cos 40^{\circ} = -20$$

$$\overline{\sigma_{12}} (-\sin 40^{\circ}) + \sigma_{22} \cos 40^{\circ} = 0$$

$$\overline{\sigma_{11}} = -20 - \tau_{12} \cos 40^{\circ} = 0$$

$$\overline{\sigma_{11}} = -20 - \tau_{12} \cos 40^{\circ} = 49.37 \text{ MPa} \frac{v_2}{v_2}$$

- 2) Generally, the state of stress can vary from point to point. Therefore, σ_{rr} , σ_{00} , σ_{zz} , τ_{z0} , $\tau_{rz} \rightarrow f(r, 0, z)$
- Due to symmetry about z-axis, there would be no variation of any stresses along z-direction and O-direction

$$\therefore \quad \sigma_{rr}, \ \sigma_{oo}, \ \sigma_{zz}, \ \tau_{zo}, \ \tau_{ro}, \ \tau_{rz} \rightarrow f(r) \qquad (12)$$

 $\sigma_{rr} = \tau_{rz} = constant (due to negligible variation across in cylindrical wall)$

But,
$$\sigma_{rr} |_{inner wall} = \tau_{rz} = \sigma_{rr} |_{outer wall} = constant$$

 $\therefore \sigma_{rr} |_{outer face} = o | wall |_{r-face} |_{r-face}$

At the joint of the end caps to the cylindrical wall,



V_r=0 (else one side should bulge out and other side should bulge in) Using force equilibrium in z-direction:

 $\stackrel{+}{\rightarrow} \sum F_z = 0$

$$\Rightarrow \sigma_{zz} (2\pi rt) = P\pi r^{2}$$
$$\Rightarrow \sigma_{zz} = \frac{Pr}{2t} - \frac{1}{1}$$

 $z = c_{z0} = 0 - (\gamma_2)$

(since there is no twisting moment about Z)



$$3 \ (a) \left[\underbrace{\Phi}_{ev} \right] = \begin{bmatrix} 55 & 0 & 24 \\ 0 & 46 & 0 \\ 24 & 0 & 43 \end{bmatrix} - 48 \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} = \begin{bmatrix} 7 & 0 & 24 \\ 0 & -2 & 0 \\ 24 & 0 & -5 \end{bmatrix} \qquad \boxed{Y_2}$$

(b)
$$I_{1}(\sigma) = |44 | \sqrt{4}$$

 $I_{2}(\sigma) = |55 | 0 | + |46 | 0 | + 55 | 24 | 0 | 43 | + 24 | 43 |$
 $= 8530 + 1978 + 1789 | \sqrt{4}$
 $I = 6297 | \sqrt{4} | \sqrt{4}$
 $I_{3}(\sigma) = det([\underline{0}]) = 82294 | \sqrt{2}$

$$I_{1}(\sigma_{dev}) = 0 \frac{V_{4}}{4}$$

$$I_{2}(\sigma_{dev}) = -615 \frac{V_{4}}{4}$$

$$I_{3}(\sigma_{dev}) = 1222 \frac{V_{2}}{2}$$

(c)

$$(55,24)$$
We can draw Mohr's circle for

$$(24,26,0)$$

$$(49,0)$$

$$(73,74,0)$$
We can draw Mohr's circle for

$$(2)$$

$$(24,26,0)$$

$$(49,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$

$$(73,74,0)$$



Principal directions remain the same !

Alternatively,

$$\begin{bmatrix} \underline{n}_1 \end{bmatrix} = \begin{bmatrix} \cos \Theta_1 \\ \Theta \\ \sin \Theta_1 \end{bmatrix}, \begin{bmatrix} \underline{n}_2 \end{bmatrix} = \begin{bmatrix} \Theta \\ I \\ \Theta \end{bmatrix}, \begin{bmatrix} \underline{n}_3 \end{bmatrix} = \begin{bmatrix} \cos \Theta_2 \\ \Theta \\ \sin \Theta_2 \end{bmatrix}$$

(e) Principal shresses for $[\underline{O}] \rightarrow 73.74, 46, 24.26$

Absolute max shear stress = $\frac{73.74 - 24.26}{2}$ [1] = 24.74

Principal stresses = 25.74, -2, -23.74 of deviatoric state

Absolute max shear stress = $\frac{25 \cdot 74 - (-23 \cdot 74)}{2}$ $= 24 \cdot 74$

They are same!

4) 0.5 mark for each correct figure





Integrate the normal strains Exx and Eyy

$$\frac{\partial u_x}{\partial x} = \epsilon_{xx} \Rightarrow u_x(x,y) = \frac{Px^2y}{2EL} + g(y) - 1$$

$$\frac{\partial u_{Y}}{\partial y} = -\nu \in_{xx} \Rightarrow u_{Y}(x, y) = -\nu \frac{P_{xy}}{a \in I} + h(x) - 2$$

From shear strain, we find

$$\frac{\partial u_{z}}{\partial y} + \frac{\partial u_{y}}{\partial z} = 2 \epsilon_{xy} = \frac{P}{2GI} (h^{2} - y^{2})$$

which yields using () and (2)

$$\frac{Px^{2}}{aEI} + \frac{dg}{dy} - \frac{vPy^{2}}{aEI} + \frac{dh}{dx} = \frac{P}{2GI} (h^{2}-y^{2}) \left(\frac{1}{2}\right)$$

Reamanging the terms, we get:

The above equation is of the form H(x) = G(y). Hence, it must be that H(x) = G(y) = C (constant) (1) Therefore, integrating the LHS and RHS, we get

LHS:
$$\frac{Px^2}{AEI} + \frac{dh(x)}{dx} = C \Rightarrow h(x) = Cx - \frac{Px^3}{6EI} + \frac{P_1}{6EI}$$

RHS:
$$\frac{P}{2GI}(h^2-y^2) + \frac{VPy^2}{REI} - \frac{dg(y)}{dy} = c$$

$$\Rightarrow g(y) = -Cy + \frac{P}{2GI} \left(h^2y - \frac{y^3}{3}\right) + \frac{vPy^3}{6EI} + D_2$$

Putting these values in the displacement expressions, we get: $u_{x}(x,y) = \frac{Px^{2}y}{aEE} + \frac{P}{2GE} \left(h^{2}y - \frac{y^{3}}{3}\right) + \frac{vPy^{3}}{6EE} - Cy + D_{2}$ $u_{y}(x,y) = -\frac{Px^{3}}{6EE} - \frac{vPxy^{2}}{REE} + Cx + D_{1}$

Now, use the displacement boundary conditions

$$u_{z} |_{(L,0)} = 0 \implies D_{z} = 0$$

$$u_{y} |_{(L,0)} = 0 \implies D_{1} = -CL + \frac{PL^{3}}{6EL}$$

$$\frac{\partial u_y}{\partial x}\Big|_{(L,0)} = 0 \implies -\frac{PL^2}{2EL} + C = 0 \implies C = \frac{PL^2}{2EL}$$

$$D_1 = -\frac{PL^3}{3E^2}$$
, $D_2 = 0$, $C = \frac{PL^2}{4EI}$
(1.5)

For plane strain case, five strain-compatibility equations are naturally satisfied. You will also find that

$$\frac{\partial^2 \epsilon_{11}}{\partial y^2} + \frac{\partial^2 \epsilon_{22}}{\partial x^2} = \frac{\partial^2 \epsilon_{12}}{\partial x \partial y}$$
 is also satisfied!

Q6. A thin rectangular sheet is strained with uniform strain components: $\epsilon_{xx} = 0.001$, $\epsilon_{yy} = -0.001$, $\gamma_{xy} = 0.001$. All other strain components are zero implying it is a plane strain condition.

(i) Draw Mohr's circle for this case.

(ii) How much will be the percentage change in the area of thin sheet?

(iii) Which line elements undergo maximum and minimum longitudinal/normal strain?

(iv) What will be the orientation of the two perpendicular lines in the plane of sheet which undergo maximum angle change between them?

Solution:

 $\epsilon_{xx} = 0.001, \ \epsilon_{yy} = 0.001, \ \gamma_{xy} = 0.001$, others are all zero!



for drawing Mohr's circle orrectly

(i) The Mohr's circle is drawn above.

Center of the circle =
$$\frac{\epsilon_{xx} + \epsilon_{yy}}{2} = 0$$

Radius = $\sqrt{\left(\frac{\epsilon_{xx} - \epsilon_{yy}}{2}\right)^2 + \left(\frac{\gamma_{xy}}{2}\right)^2}$
= $\sqrt{0.001^2 + \frac{0.001^2}{4}}$
= $0.001\frac{\sqrt{5}}{2}$

(ii) Percentage change in area of the sheet = $(\epsilon_{xx} + \epsilon_{yy}) \times 100 = 0\%$

- (iii) To find line elements undergoing max. and min. longitudinal strain (principal strains), we use the Mohr's circle. The principal strains are:
 - $\frac{\epsilon_{xx} + \epsilon_{yy}}{2} + R = R$: the line element that undergoes <u>maximum longitudinal strain</u> lie along the normal of maximum principal strain plane. Its normal is oriented at

$$2\theta = \tan^{-1}\left(\frac{1}{2}\right) \text{ clockwise from X-axis in Mohr's cirle}$$

$$\Rightarrow \theta = \frac{1}{2}\tan^{-1}\left(\frac{1}{2}\right) \text{ anti-clockwise from X-axis physically. } \boxed{122}$$

• $\frac{\epsilon_{xx} + \epsilon_{yy}}{2} - R = -R$; the line element that undergoes minimum longitudinal strain lie along the normal of minimum principal strain plane. Its normal is oriented at

$$\pi + 2\theta = \pi + \tan^{-1}\left(\frac{1}{2}\right) \text{ clockwise from X-axis in Mohr's cirle}$$
$$\Rightarrow \frac{\pi}{2} + \theta = \frac{\pi}{2} + \frac{1}{2}\tan^{-1}\left(\frac{1}{2}\right) \text{ anti-clockwise from X-axis physically.}$$

- (iv) Maximum shear strain will occur between those two line elements which correspond to top and bottom points in the circle. The corresponding directions are:
 - First line element oriented along

$$\left(\frac{\pi}{2} - 2\theta\right)$$
 anti-clockwise from X-axis in Mohr's circle
 $\Rightarrow \left(\frac{\pi}{4} - \theta\right)$ clockwise from X-axis physically $\left[\frac{1}{2}\right]$

• Second line element oriented along

